

# GRABO PLANK*IT* SPC

CLICK LVT FLOORING

Qty/Box  
~2.1677m<sup>2</sup>  
10 PIECES

Plank size  
177.8  
x  
1219.2  
mm

Thickness  
5.0 mm  
Wear layer  
0.55 mm

  
33

  
42

  
iGuard

## SPECIFICATION

CONSTRUCTION	SPC Click LVT	
PLANK SIZE	EN ISO 24341	177.8 x 1219.2 mm
	EN ISO 24341	7x48 inch
THICKNESS	EN ISO 24346	5.0 mm
WEAR LAYER THICKNESS	EN ISO 24340	0.55 mm
TOTAL WEIGHT	EN ISO 23997	9.9 kg/m <sup>2</sup>

## CLASSIFICATION

BINDER CONTENT	EN ISO 10582	Type I.
EUROPEAN CLASSIFICATION	EN ISO 10582	class: 33/42
RESIDUAL INDENTATION	EN ISO 24343	max. 0.1 mm
DIMENSIONAL STABILITY	EN ISO 23999	max. 0.1%
CURLING	EN ISO 23999	max. 2.0 mm

## PERFORMANCE

ABRASION GROUP	MSZ EN 660-2	class: T
FIRE RESISTANCE	EN 13501-1	class: Bfl-s1
SLIP RESISTANCE	EN 13893	DS
	DIN 51130	R10
LIGHT FASTNESS	EN ISO 105-B02	grade 6
CHEMICAL RESISTANCE	EN ISO 26987	✓
SURFACE TREATMENT	iGuard PUR Surface	
ENVIRONMENTAL ATTRIBUTES	solvent and phthalate free	
CONTENT OF PCP	EN 12673	does not contain
FORMALDEHIDE EMISSION	ENV 717-1	E1 (no emission)

GRABOPLAST

FLOOR COVERING MANUFACTURERS LTD.

H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-100

[www.graboplast.com](http://www.graboplast.com)

 [www.facebook.com/graboplast](https://www.facebook.com/graboplast)

