

GRABO Silver Knight Wall

SELF-DISINFECTIVE FLEXIBLE WALL COVERING


RECOMMENDED USAGE

- > Education
- > Healthcare
- > Retail
- > Hospitality
- > Offices

PERFORMANCE, FEATURES & BENEFITS

Eliminates harmful pathogens without chemicals | Flexibility
Dimensionally stable | 1.5 m width

CONSTRUCTION



SPECIFICATIONS

DESCRIPTION


Construction	heterogeneous wall covering	
Total thickness	EN ISO 24346	1,5 mm
Wear layer thickness	EN ISO 24340	0,2 mm
Width of roll	EN ISO 24341	1,5 m
Length of roll	EN ISO 24341	25 lm
Total weight	EN ISO 23997	1,5 kg/m ²

CLASSIFICATION

Residual indentation	EN 433	max. 0.35 mm
Dimensional stability	EN ISO 23999	max. 0,2 %
Light fastness	EN ISO 105-B02	grade 6

PERFORMANCE

Abrasion group	MSZ EN 660-1	T
Chemical resistance	EN ISO 26987	✓
Surface treatment	TechSurface	
Anti bacterial and fungicid treatment	Silver Knight	
Seaming method	EN ISO846:1999	heat or cold weld




TOTAL THICKNESS



TOTAL WEIGHT



WIDTH OF ROLLS



SILVER KNIGHT WALL